

# Cresto, Core Single-Flex H 1507

## Fall arrest lanyard 1507

- Singel fall arrest lanyard
- 60 mm hooks
- 30 mm flexible webbing



EN 355 : 2002

### Product description

A single fall arrest lanyard provides secure protection when working on skylifts and scaffolding. Core Single-Flex has the same functions as Core Twin-Flex except that it has only one webbing and one hook instead of two. Core Single-Flex is manufactured as a flexible tube with internal elasticity, which allows you to stretch the line to a maximum length. At the beginning of the rope there is an external absorber mounted which is released in case of a fall and catches you. Tested and approved for users up to 100 kg. The cover on the absorber can easily be replaced if it becomes dirty or damaged to ensure that the rope underneath is protected in the best way.

### Product properties

|                                      |                                |
|--------------------------------------|--------------------------------|
| Brand                                | Cresto                         |
| Attaching connector 1                | Oval screwgate steel carabiner |
| Attaching connector 2                | Big hook with 60 mm opening    |
| Minimum breaking strength - MBS (kN) | 15                             |
| Energy absorber                      | Yes                            |
| Fall indicator                       | Yes                            |
| Maximum load (kg)                    | 100                            |
| Min/Max load (kg)                    | 40/100                         |
| Maximum number of users              | 1                              |
| Mechanics                            | Tear-webbing absorber          |
| Maximum working temperature (c)      | 100                            |
| Minimum working temperature (c)      | -40                            |
| PPE-category                         | Category 3                     |

|                           |                                                                              |
|---------------------------|------------------------------------------------------------------------------|
| Declaration of Conformity | Yes                                                                          |
| EN-standard               | EN 355 : 2002                                                                |
| Warranty                  | 2+1 year when registered in Inspector                                        |
| Identification            | Serial number                                                                |
| Annual inspection         | Yes, every 12 months                                                         |
| Life span                 | 10 + 2 years. Product lifecycle 10 years + 2 years stock keeping             |
| Notified body             | 1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic |
| RFID                      | No                                                                           |

## Article information

| Article number | Article name                       | GTIN          | UNSPSC Code | Country of origin |
|----------------|------------------------------------|---------------|-------------|-------------------|
| 012203772      | Cresto, Core Singel-Flex H<br>1507 | 7350015791251 | 46182302    | Slovakia          |