

CRESTO, CORE TWIN-FLEX H 1508

Fall arrest lanyard 1508

- Twin fall arrest lanyard
- 60 mm hooks
- 30 mm flexible webbing

Standards: **EN 355 : 2002**



Product description

A double fall arrest lanyard where the user moves alternately.

A double fall arrest lanyard is designed to suit you who need to move when you work at heights. With double hooks, you always have a hook anchored when you move with the other hook. This is to provide the optimal security on, for example, scaffolding, mobile platforms or industries. Worker Twin-Flex is manufactured as a flexible tube with internal elasticity, which allows you to stretch the line to a maximum length. At the beginning of the rope, there is an external absorber mounted which is released in case of a fall and catches you. Tested and approved for users up to 100 kg. The cover on the absorber can easily be replaced if it becomes dirty or damaged to ensure that the rope underneath is protected in the best way.

Product properties

Brand:	Cresto
Min/Max load (kg):	40/100
Maximum load (kg):	100
Maximum number of users:	1
Minimum working temperature (c):	-40
Maximum working temperature (c):	100
EN-standard:	EN 355 : 2002
Notified body:	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic
Annual inspection:	Yes, every 12 months
Life span:	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping
RFID:	No
Warranty:	2+1 year when registered in Inspector
Declaration of Conformity:	Yes
Fall indicator:	Yes
Minimum breaking strength - MBS (kN):	15

Energy absorber:	Yes
Attaching connector 1:	Oval screwgate steel carabiner
Attaching connector 2:	Big hook with 60 mm opening
Mechanics:	Tear-webbing absorber

Reference	Article name	Size (m)	Colors	GTIN	Country of origin
012203782	Cresto, Core Twin-Flex H, 2m	1.8	YELLOW	7350015791268	Slovakia