

CRESTO, CORE SINGLE-FLEX H 1507

Fall arrest lanyard 1507

- Singel fall arrest lanyard
- 60 mm hooks
- 30 mm flexible webbing

Standards: **EN 355 : 2002**



Product description

A single fall arrest lanyard with flexible webbing and hooks.

A single fall arrest lanyard provides secure protection when working on skylifts and scaffolding. Core Single-Flex has the same functions as Core Twin-Flex except that it has only one webbing and one hook instead of two. Core Single-Flex is manufactured as a flexible tube with internal elasticity, which allows you to stretch the line to a maximum length. At the beginning of the rope there is an external absorber mounted which is released in case of a fall and catches you. Tested and approved for users up to 100 kg. The cover on the absorber can easily be replaced if it becomes dirty or damaged to ensure that the rope underneath is protected in the best way.

Product properties

ProductPdfTemplate:	Cresto Safety Product PDF
Brand:	Cresto
Min/Max load (kg):	40/100
Maximum load (kg):	100
Maximum number of users:	1
Minimum working temperature (c):	-40
Maximum working temperature (c):	100
EN-standard:	EN 355 : 2002
Notified body:	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic
Annual inspection:	Yes, every 12 months
Life span:	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping
RFID:	No
Warranty:	2+1 year when registered in Inspector
Declaration of Conformity:	Yes
Fall indicator:	Yes

Minimum breaking strength - MBS (kN):	15
Energy absorber:	Yes
Attaching connector 1:	Oval screwgate steel carabiner
Attaching connector 2:	Big hook with 60 mm opening
Mechanics:	Tear-webbing absorber

Reference	Article name	Size (m)	GTIN	Country of origin
012203772	Cresto, Core Singel-Flex H 1507	1.8	7350015791251	Slovakia