

CRESTO, CORE SINGLE-WEB H 1505

Fall arrest lanyard 1505

- Singel fall arrest lanyard
- 60 mm hooks
- 20 mm webbing

Standards: **EN 355 : 2002**



Product description

A single fall arrest lanyard with webbing and one hook.

A single fall arrest lanyard provides secure protection when working on skylifts and scaffolding. Energy Single-web has the same functions as Energy Twin-web except that it has only one webbing and one hook instead of two. Energy Single-web is manufactured as a tube with internal core. At the beginning of the webbing there is an external absorber mounted which is released in case of a fall and catches you. Tested and approved for users up to 100 kg. The cover on the absorber can easily be replaced if it becomes dirty or damaged to ensure that the rope underneath is protected in the best way. the bag make it easy to carry out an annual inspection according to EN 365

Product properties

Brand:	Cresto
Min/Max load (kg):	40/100
Maximum load (kg):	100
Maximum number of users:	1
Minimum working temperature (c):	-40
Maximum working temperature (c):	100
EN-standard:	EN 355 : 2002
Notified body:	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic
Annual inspection:	Yes, every 12 months
Life span:	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping
RFID:	No
Warranty:	2+1 year when registered in Inspector
Declaration of Conformity:	Yes
Fall indicator:	Yes
Minimum breaking strength - MBS (kN):	15

Energy absorber:		Yes			
Attaching connector 1:		Oval screwgate steel carabiner			
Attaching connector 2:		Big hook with 60 mm opening			
Mechanics:		Tear-webbing absorber			
Reference	Article name	Size (m)	Colors	GTIN	Country of origin
012203752	Core, Single-Web H	2	BLACK	7350015791213	Slovakia