## **A CRESTO SAFETY**

## CRESTO, SIMO H-A 2343

## **Work Positioning Lanyard 2343**

- · ANSI certified carabiner and hook
- Strong against sharpe edges
- Durable 12 mm polyamide rope

Standards:

EN 354 : 2010

EN 358 : 1999

EN 795 : 2012



## **Product description**

A work positioning lanyard with a simple one-hand adjustment and ANSI certified carabiner and hook.

Simo H-A is a work positioning lanyard of a strong polyamide rope of the highest quality. With its smooth rope grab you can easily adjust the tension in the rope with one hand. This lanyard is tested and approved for users up to 140 kg and is unique thanks to its certification for many environments and standards.

The difference between Simo H-A and Simo S is that this model has ANSI certified carabiner and a big ANSI certified hook with 64 mm opening.

Product properties	
Brand:	Cresto
Material:	Polyamide
Maximum load (kg):	140
Maximum number of users:	1
Minimum working temperature (c):	-40
Maximum working temperature (c):	100
EN-standard:	EN 354 : 2010, EN 358 : 1999, EN 795 : 2012
Notified body:	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic
Annual inspection:	Yes, every 12 months
Life span:	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping
RFID:	Yes
Warranty:	2+1 year when registered in Inspector
Declaration of Conformity:	Yes
Rope:	12 mm kern mantle rope in polyamide by the brand Patron from Teufelberger
Fall indicator:	No

Attaching connector 2:		Big ANSI certified aluminum hook with 64 mm opening				
Adjustable under load:		Yes				
Reference	Article name		Size (m)	Colors	GTIN	Country of origin
012204040	Cresto, Simo H-A, 1,5 m, red		1.5	RED	7350015796157	Slovakia
012204041	Cresto, Simo H-A, 2 m, red		2	RED	7350015796164	Slovakia
012204042	Cresto, Simo H-A, 5 m, red		5	RED	7350015796171	Slovakia
012204043	Cresto, Simo H-A, 10 m, red		10	RED	7350015796188	Slovakia
012204045	Cresto, Simo H-A, 30 m, red		30	RED	7350015796201	Slovakia

ANSI certified trippellock carabiner in aluminum

15

No

Minimum breaking strength - MBS (kN):

Energy absorber:

Attaching connector 1: